



PRODUCT FEATURES

SPIROMETRY FILTER 59 "PLUS"

For use during pulmonary lung function testing

Description: Barrier filtration for protection of patient, staff and equipment from bacterial and viral contamination.
Filter with "**small soft anatomical mouthpiece**" to allow adequate blockage of mouth while avoiding possible leaks and dispersion from the sides of the mouth itself.

Code items:

- individually packaged: **30821**

Materials:

- housing: Polystyrene (HIPS) *recyclable*
- filtration membrane: Hydrophobic Polypropylene (SMS)
- mouthpiece: Soft PVC (non-toxic)

Kind of filtration: Electrostatic / Mechanical

Flow resistance: (complies with ATS)


- flow rate 12,00 l/s 0,93 cm H₂O / (l/s)

Cross Contamination Reduction Efficiency: > 99,99 %

Dead space: 32,00 ml
(connector not included)

Filtration area: 25,62 cm²
Exchange filtration area: > 72,00 cm²

Weight: 29,00 g

Working procedure  0373 Class IIa - Italian Superior Institute of Health
Disposable

Quantity / box: 75 pcs.

NOTES: single patient use. Latex free. Medical Devices Regulations - Directive 93/42/EEC

Any size of adaptors is available upon request.



MADA

Spirometry Filters