

PRODUCT FEATURES

SPIROMETRY FILTER 83 - B

For use during pulmonary lung function testing with: MicroMedical/Microlab – Mir - Vitalograph spirometers

Description: Barrier filtration for protection of patient, staff and equipment from bacterial and viral contamination.

Filter "oval shape" to allow adequate blockage of mouth while avoiding possible leaks and dispersion

from the sides of the mouth itself.

Code item:

- individually packaged: 30887 ADULT - PAEDIATRIC

Materials:

housing: Polystyrene (HIPS) <u>recyclable</u>
 filter media: Hydrophobic Polypropylene TECHN 200

- sealed: Ultrasonically

Kind of filtration: Electrostatic / Mechanical

Flow resistance: (complies with ATS)

- flow rate 14,00 L/sec < 0,79 cm H₂O / (L/s)

Bacterial Filtration Efficiency:

Flow rate 30 L/min * 99,999 % Flow rate 750 L/min * 99,9 %

Viral Filtration Efficiency:

Flow rate 30 L/min * 99,99 % Flow rate 750 L/min * 99,99 %

Dead space: 38,20 ml (connector not included)

Filtration area: 53,75 cm²

Weight: 34,00 gr

Working procedure: Class Ila - Eurofins

Disposable

Quantity / box: 100 pcs.

* HPA, CEPR Biosafety Investigation Unit - UK - Coronati Consulting: BIOCOMPATIBILITY TESTS

NOTE: single patient use PVC and Latex free

Medical Device Regulations – Directive 93/42/EEC

MADA